




datalab****

data is everywhere, value is hidden

Relational Databases

Lecturer: Азат Якупов (Azat Yakupov)

<https://datalaboratory.one>



“All information in the database must be cast explicitly in terms of values in relations and in no other way”

Information Principle




- Data Definition Language (~ DDL)
- Data Integrity (~ database constraints)
- Data Manipulation Language (~ DML)


ID	Person
1	Ivan Ivanov




ID	Hobby	PersonId
1	music	1
2	blog	1





ID	Person	Hobbies
1	Ivan Ivanov	<pre><hobbies> <item value =“music” /> <item value =“blog” /> </hobbies></pre>



ID	Person	Hobbies	
1	Ivan Ivanov	ID	Hobby
		1	music
		2	blog



ID	Person	Hobbies
1	Ivan Ivanov	<pre>{ "hobbies": [{"value": "music"}, {"value": "blog"}] }</pre>




Dimensional Table	
column1	<i>type1</i>
column2	<i>type2</i>

Dimensional Table	
column1	<i>type1</i>
column2	<i>type2</i>



Dimensional Table	
column1	<i>type1</i>
column2	<i>type2</i>


Fact Table	
cell1	<i>type1</i>
cell2	<i>type2</i>
cell3	<i>type1</i>
cell4	<i>type3</i>

Dimensional Table	
column1	<i>type1</i>
column2	<i>type2</i>






MOLAP Cube







MOLAP “manifold”











- Rotate
- Drill Up
- Drill Down

Drill Up




```
SELECT provider,  
       count(product)  
FROM table_fact  
GROUP BY provider
```

Rotate + Drill Up




```
SELECT product,  
       count(provider)  
FROM table_fact  
GROUP BY product
```

Drill Down



```
SELECT *  
FROM table_fact
```





provider	product	amount
s1	p1	300
s1	p2	200
s2	p1	300
s2	p2	400
s3	p2	200
s4	p2	200

SELECT **sum**(amount) **AS** sm
FROM delivery

sm
1600



provider	product	amount
s1	p1	+ 300
s1	p2	+ 200
s2	p1	+ 300
s2	p2	+ 400
s3	p2	200
s4	p2	200

```

SELECT provider,
       sum(amount) AS sm
FROM delivery
GROUP BY provider
ORDER BY provider

```

provider	sm
s1	500
s2	700
s3	200
s4	200



provider	product	amount
s1	p1	300
s1	p2	200
s2	p1	300
s2	p2	400
s3	p2	200
s4	p2	200

```

SELECT product,
       sum(amount) AS sm
FROM delivery
GROUP BY product
ORDER BY product
  
```

product	sm
p1	600
p2	1000



provider	product	amount
s1	p1	300
s1	p2	200
s2	p1	300
s2	p2	400
s3	p2	200
s4	p2	200

```

SELECT provider, product,
       sum(amount) AS sm
FROM delivery
GROUP BY provider, product
ORDER BY provider, product

```

provider	product	amount
s1	p1	300
s1	p2	200
s2	p1	300
s2	p2	400
s3	p2	200
s4	p2	200



provider	product	amount
s1	p1	+ 300
s1	p2	+ 200
s2	p1	+ 300
s2	p2	+ 400
s3	p2	200
s4	p2	200

```

SELECT provider,
       sum(amount) AS sm
FROM delivery
GROUP BY provider
HAVING sum(amount) > 300
ORDER BY provider

```

provider	sm
s1	500
s2	700



provider	product	amount
s1	p1	+ 300
s1	p2	+ 200
s2	p1	+ 300
s2	p2	+ 400
s3	p2	200
s4	p2	200

```

SELECT provider,
sum(amount) FILTER
(WHERE amount>300) AS sm
FROM delivery
GROUP BY provider
ORDER BY provider
  
```

provider	sm
s1	<i>null</i>
s2	400
s3	<i>null</i>
s4	<i>null</i>



provider	product	amount
s1	p1	300
s1	p2	200
s2	p1	300
s2	p2	400
s3	p2	200
s4	p2	200





```

SELECT provider,
       sum(amount) AS sm
FROM delivery
GROUP BY provider
ORDER BY sm DESC
LIMIT 2

```






Student	
Name	ID*
Ivan	1
Anna	2
Peter	3
Kate	4

Student_Fun	
StudentID*	FunID*
1	1
1	3
2	1
2	2
4	3

Fun	
Name	ID*
Party	1
Disco	2
Library	3



Student		
Name	ID*	From
Ivan	1	01.09.2022
Anna	2	01.09.2022
Peter	3	01.09.2021
Kate	4	01.09.2020

```

SELECT *
FROM student
WHERE From >= '01.09.2021'

```



```
SELECT *  
FROM fun  
WHERE From >= '01.01.0000'
```

Fun		
Name	ID*	From
Party	1	01.09.1982
Disco	2	01.09.1960
Library	3	01.01.0000

Student_Fun		
StudentID*	FunID*	From
1	1	01.02.2021
1	3	01.01.2019
2	1	01.09.2022
2	2	01.09.2022
4	3	01.09.2020

```
SELECT *  
FROM student_fun  
WHERE From >= '01.01.2020'
```

Student			
Name	ID*	From*	To*
Ivan	1	01.09.2022	01.09.2023
Anna	2	01.09.2022	<i>null</i>
Peter	3	01.09.2021	<i>null</i>
Kate	4	01.09.2020	01.09.2025
Ivan	1	02.09.2023	<i>null</i>

SELECT *
FROM student
WHERE To IS NULL

Student			
Name	ID*	From*	To*
Ivan	1	01.09.2022	01.09.2023
Anna	2	01.09.2022	<i>null</i>
Peter	3	01.09.2021	<i>null</i>
Kate	4	01.09.2020	01.09.2025
Ivan	1	02.09.2023	<i>null</i>

SELECT *
FROM student
WHERE now() BETWEEN
From AND To

Student_Fun			
StudentID*	FunID*	From*	To*
1	1	01.02.2021	31.05.2021
1	3	01.01.2019	31.05.2019
2	1	01.09.2022	31.12.2022
2	2	01.09.2022	<i>null</i>
4	3	01.09.2020	<i>null</i>

SELECT *
FROM student_fun
WHERE now() BETWEEN
From AND To

SELECT *
FROM fun
WHERE now() BETWEEN
From AND To




Fun			
Name	ID*	From*	To*
Party	1	01.09.1982	01.01.9999
Disco	2	01.09.1960	01.01.9999
Library	3	01.01.0000	01.01.9999

Student			
Name	ID*	From*	To*
Ivan	1	01.09.2022	01.09.2023
Anna	2	01.09.2022	<i>null</i>
Peter	3	01.09.2021	<i>null</i>
Kate	4	01.09.2020	01.09.2025
Ivan	1	02.09.2023	<i>null</i>



Student		
Name	ID*	During*
Ivan	1	[01.09.2022 : 01.09.2023]
Anna	2	[01.09.2022 : 01.01.9999]
Peter	3	[01.09.2021 : 01.01.9999]
Kate	4	[01.09.2020 : 01.09.2025]
Ivan	1	[02.09.2023 : 01.01.9999]

$$i_1 = [b_1 : e_1], i_2 = [b_2 : e_2]$$



$$i_1 = [b_1 : e_1], i_2 = [b_2 : e_2]$$

$$i_1 = i_2 \Rightarrow b_1 = b_2 \text{ AND } e_1 = e_2$$

$$i_1 \supseteq i_2 \Rightarrow b_1 \leq b_2 \text{ AND } e_1 \geq e_2$$

$$i_1 \supset i_2 \Rightarrow i_1 \supseteq i_2 \text{ AND } i_1 \neq i_2$$

$$i_1 \text{ BEFORE } i_2 \Rightarrow e_1 < b_2;$$

$$i_1 \text{ AFTER } i_2 \equiv i_2 \text{ BEFORE } i_1$$

$$i_1 = [b_1 : e_1], i_2 = [b_2 : e_2]$$

$$i_1 \text{ MEETS } i_2 \Rightarrow b_2 = e_1 + 1 \text{ OR } b_1 = e_2 + 1$$


$$i_1 \text{ OVERLAPS } i_2 \Rightarrow b_1 \leq e_2 \text{ AND } b_2 \leq e_1$$

$$i_1 \text{ MERGES } i_2 \Rightarrow i_1 \text{ OVERLAPS } i_2 \\ \text{OR } i_1 \text{ MEETS } i_2$$




$$i_1 \text{ BEGINS } i_2 \Rightarrow b_1 = b_2 \text{ AND } e_1 \leq e_2$$

$$i_1 \text{ ENDS } i_2 \Rightarrow e_1 = e_2 \text{ AND } b_1 \geq b_2$$


$$i_1 = [b_1 : e_1], i_2 = [b_2 : e_2]$$



$$i_1 = [b_1 : e_1], i_2 = [b_2 : e_2]$$



$$i_1 = [b_1 : e_1], i_2 = [b_2 : e_2]$$



$$i_1 = [b_1 : e_1], i_2 = [b_2 : e_2]$$

$$i_1 \text{ UNION } i_2 \Rightarrow [\text{MIN}(b_1, b_2) : \text{MAX}(e_1, e_2)]$$

$$i_1 \text{ UNION } i_2 \Rightarrow (i_1 \text{ MERGES } i_2) = \text{True}$$

$$i_1 \text{ INTERSECT } i_2 \Rightarrow [\text{MAX}(b_1, b_2) : \text{MIN}(e_1, e_2)]$$

$$i_1 \text{ INTERSECT } i_2 \Rightarrow (i_1 \text{ OVERLAPS } i_2) = \text{True}$$

$$i_1 \text{ MINUS } i_2 \Rightarrow [b_1 : \text{MIN}(b_2 - 1, e_1)] \mid b_1 < b_2 \text{ AND } e_1 \leq e_2 \\ [\text{MAX}(e_2 + 1, b_1) : e_1] \mid b_1 \geq b_2 \text{ AND } e_1 > e_2$$

CREATE TABLE reservation (
 during **TSTZRANGE**,
 EXCLUDE USING GIST (during WITH &&)
);

INSERT INTO reservation VALUES
('['2023-01-01 11:30, 2023-01-15 15:00)');

INSERT INTO reservation VALUES
('['2023-01-15 15:01, 2023-01-16 15:00]');

SELECT *
FROM reservation;

During
["2023-01-01 11:30:00+00", "2023-01-15 15:00:00+00")
["2023-01-15 15:01:00+00", "2023-01-16 15:00:00+00"]

SELECT *

FROM reservation

WHERE during @>

‘[2023-01-01 11:30, 2023-01-12 15:00]’;

During

["2023-01-01 11:30:00+00", "2023-01-15 15:00:00+00")

Entities

Attributes

Values



Entities	
Name	ID*
...	...

Attribute_Values			
ID*	e_id	a_id	value
...	...	...	...
...	...	...	...

Attributes	
Name	ID*
...	...

Products	
Name	ID*
TV	1
Fridge	2

Products_Properties			
ID*	e_id	a_id	value
1	1	1	25
2	1	2	true
3	2	3	-15
4	2	1	60

Properties	
Name	ID*
weight	1
is_led	2
min_temp	3

EAV model

(Entity-Attribute-Value)

user_id	key	value
1	first_name	Petr
1	last_name	Petrov
2	first_name	Ivan
2	last_name	Ivanov
...	...	...



Relational model


user_id	first_name	last_name	...
1	Petr	Petrov	...
2	Ivan	Ivanov	...



Indicator	
Name	ID*
boiler	1


Indicator_Property				
ID*	i_id	p_id	value	time
1	1	100	100	12:50
2	1	100	98	12:51
3	1	100	105	12:52
4	1	100	97	12:53

Property	
Name	ID*
temperature	100




```
SELECT value, time
FROM Indicator_Property
WHERE i_id = 1 AND p_id = 100
ORDER BY time;
```



value	time
100	12:50
98	12:51
105	12:52
97	12:53




```
SELECT i.name, p.name, value, time  
FROM Indicator_Property ip  
INNER JOIN indicator i ON  
i.id = ip.i_id  
INNER JOIN property p ON  
p.id = ip.p_id  
ORDER BY time;
```


i.name	p.name	value	time
boiler	temperature	100	12:50
boiler	temperature	98	12:51
boiler	temperature	105	12:52
boiler	temperature	97	12:53
boiler	pressure	56	12:50
boiler	pressure	34	12:51
boiler	pressure	45	12:52
boiler	pressure	78	12:53







1st level



2nd level



3rd level

```
CREATE TABLE managers  
( ID SERIAL PRIMARY KEY,  
  NAME VARCHAR NOT NULL,  
  POST VARCHAR NOT NULL,  
  MANAGER_ID INTEGER,  
  
  CONSTRAINT manager_fk  
  FOREIGN KEY (MANAGER_ID)  
  REFERENCES managers (ID)  
);
```

foreign key

id	name	post	manager_id
100	Anna	Director	<i>null</i>
200	Sergey	CTO	100
300	Kate	CDO	100
400	Ivan	Team Leader	200

```
SELECT m1.name AS manager_name,  
       m2.name  
FROM managers AS m1  
       INNER JOIN managers AS m2  
ON m1.id = m2.manager_id;
```

manager_name	name
Anna	Sergey
Anna	Kate
Sergey	Ivan

WITH RECURSIVE **_managers AS**

(

SELECT id,
manager_id,
name,
1 **AS** level,
array[name] **AS** path

FROM managers

WHERE manager_id **IS NULL**

UNION

SELECT m1.id,
m1.manager_id,
m1.name,
level + 1 **AS** level,
path || m1.name **AS** path

FROM managers **AS** m1 **INNER JOIN**

_managers AS m2 **ON** m1.manager_id = m2.id


)




SELECT name,
level,
path


FROM **_managers**

name	level	path
Anna	1	{Anna}
Sergey	2	{Anna,Sergey}
Kate	2	{Anna,Kate}
Ivan	3	{Anna,Sergey,Ivan}

Hierarchical + Temporal Models







MATCH

(a:entity),

(b:job)

WHERE a.name = 'public.block_list' **AND**

b.name = 'public.block_list'

CREATE (a)<-[r:OUTPUT]-(b)

RETURN type(r);

Relational model

id	node_1	node_2
100	Anna →	Germany
200	Munich →	Germany
300	BMW →	Munich
400	Ivan →	BMW
500	Ivan →	Anna
...	...	...

#1



Related?

THE BARRINGTON POST
MISSING PERSON TOPS AUGUST NEWS
Alan Millan disappears
Alan Millan, 30, disappeared from his home in Barrington this past Monday around 9 a.m. while going out on his jogging route at the Sherwood Forest. Friends and family recall Alan as a bright, charismatic person who would never have anyone.



#8

#3

#12



EXHIBIT #6



#10



#4

#7

EXHIBIT 2

EXHIBIT 13



eXtensible Markup Language

```
<? XML VERSION = "1.0" ?>
<STAR-MOVIE-DATA>
  <STAR>
    <NAME>Carrie Fisher</NAME>
    <ADDRESS><CITY>Hollywood</CITY></ADDRESS>
    <ADDRESS><CITY>Malibu</CITY></ADDRESS>
  </STAR>
  <MOVIE>
    <TITLE>Star Wars</TITLE>
    <YEAR>2017</YEAR>
  </MOVIE>
  <MOVIE>
    <TITLE>Star Wars II</TITLE>
  </MOVIE>
</STAR-MOVIE-DATA>
```


Document Type Definition

```
< !DOCTYPE Stars [  
  < !ELEMENT STARS (STAR*) >  
  < !ELEMENT STAR (NAME, ADDRESS+,MOVIES) >  
  < !ELEMENT NAME (#PCDATA) >  
  < !ELEMENT ADDRESS (STREET) >  
  < !ELEMENT STREET (#PCDATA) >  
  < !ELEMENT CITY (#PCDATA) >  
  < !ELEMENT MOVIES (MOVIE*) >  
  < !ELEMENT MOVIE (TITLE, YEAR) >  
  < !ELEMENT TITLE (#PCDATA) >  
  < !ELEMENT YEAR (#PCDATA) >  
]>
```

<? XML VERSION = “1.0” ?>

<! DOCTYPE Stars SYSTEM “star.dtd”>

<STAR-MOVIE-DATA>

<STAR>

<NAME>Carrie Fisher</NAME>

<ADDRESS><CITY>Hollywood</CITY></ADDRESS>

<ADDRESS><CITY>Malibu</CITY></ADDRESS>

</STAR>

<MOVIE>

<TITLE>Star Wars</TITLE>

<YEAR>2017</YEAR>

</MOVIE>

<MOVIE>

<TITLE>Star Wars II</TITLE>

<YEAR>1982</YEAR>

</MOVIE>

</STAR-MOVIE-DATA>

XPath

#get all titles of movies

/STAR-MOVIE-DATA/MOVIE/TITLE

#get a first title of movies

/STAR-MOVIE-DATA/MOVIE[1]/TITLE

#get a list of title of movies with year is 2017

/STAR-MOVIE-DATA/MOVIE [YEAR = 2017] /TITLE

XQuery

```
#a list of title movies with year is 2017  
for $x in doc("stars.xml")/STAR-MOVIE-DATA/MOVIE  
where $x/YEAR=2017  
order by $x/TITLE  
return $x/TITLE
```

```
CLASS Account = { accountNo: integer;  
                  balance: real;  
                  owner: REF Customer;  
                  deposit(a: Account, m: real);  
                }
```

```
CLASS Customer = { name: string;  
                  phone : string;  
                }
```

```
class Movie {  
  attribute string title;  
  attribute integer year;  
  attribute integer length;  
  attribute enum Film {color, BlackAndWhite} filmType;  
};
```

("Gone With the Wind", 1939, 231, BlackAndWhite)

("Star Wars. Last Jedi", 2017, 152, color)

```
class Star {  
  attribute string name;  
  attribute Struct Addr {string street, string city} address;  
  relationship Set<Movie> starredIn;  
};
```


```
class Movie {  
  attribute string title;  
  attribute integer year;  
  attribute integer length;  
  attribute enum Film {color, blackAndWhite} filmType;  
  relationship Set<Star> starsOf;  
};
```


Star	
property	type
name	string
address	address
Movie	CLASS



Movie	
property	type
title	string
year	integer
length	integer
Star	CLASS


```
class Movie {  
  attribute string title;  
  attribute integer year;  
  attribute integer length;  
  attribute enum Film {color, BlackAndWhite} filmType;  
  relationship Set<Star> starsOf;  
};
```



```
class Cartoon extends Movie {  
  relationship Set<Star> voices;  
};
```



```
class Mystery extends Movie {  
  attribute boolean isScreaming;  
};
```

```
class Cartoon extends Movie {  
relationship Set<Star> voices;  
};
```



```
class Mystery extends Movie {  
attribute boolean isScreaming;  
};
```



```
class CartoonMystery extends Mystery : Cartoon ;
```

```
class CarSharing {  
    attribute class Car;  
    attribute class Person;  
    attribute string district;  
}
```

```
class Car {  
    attribute string model;  
    attribute string regNumber;  
    attribute string status;  
}
```

```
class Person {  
    attribute string name;  
    attribute class Document;  
    attribute string phone;  
}
```

```
SELECT c.model, c.regNumber  
FROM c IN Cars  
WHERE status = 'working'
```

```
count( SELECT c.model  
        FROM c IN Cars  
        WHERE status = 'working')
```

COMMIT;

